




Images



L: 25 mm

a: 7.3 mm

b: 32.5 mm



L: 25 mm

a: 7.3 mm

b: 32.5 mm



L: 25 mm

a: 7.3 mm

b: 32.5 mm



L: 25 mm

a: 7.3 mm

b: 32.5 mm



L: 25 mm

a: 7.3 mm

b: 32.5 mm



L: 25 mm

a: 7.3 mm

b: 32.5 mm



L: 25 mm

a: 7.3 mm

b: 32.5 mm

Description

Micrómetro digital Mitutoyo impermeable de acción rápida que permite realizar mediciones varias veces más rápido que un micrómetro estándar. El armazón altamente estable incorpora un escudo térmico para preservar la precisión durante sesiones de medición prolongadas. Un dedal de trinquete garantiza una medición repetible.

Features

Digital/Analog:	Digital
Inch-Metric:	Inch/Metric
Range:	1 - 2 "
Digital step:	0.00005"/0.001 mm
Maximum Permissible Error J MPE:	±0.00005"
Flatness:	0.000012"
Parallelism:	0.00004"
Display:	LCD, character height 7.5 mm
Measuring spindle:	With spindle lock, ø6.35mm, spindle pitch 2 mm
Scale:	Thimble and sleeve satin chrome finish, ø19.3 mm
Measuring force:	7 - 12 N
Power supply:	1 battery SR-44
Battery life:	Approx. 2.4 years
Delivered:	Including box, key, 1 battery, setting standard (from 25 mm upward) certificate of inspection (0-50 mm range)
ABS / INC (INC ZERO):	Yes
Auto Power OFF after 20 min. non use:	Yes
Function lock:	Yes
HOLD:	Yes
Mass:	325 g

Dimensions

